

# HM PLATINUM SERIES



## LUMINAIRE CHARACTERISTICS

85 - 265 Vac 50-60 Hz PF  $\leq$  0.95  
 50,000 Hours Lifespan 30° C @ L70  
 Energy Savings between 50 - 75%  
 Temperature Range -20° - +55° C  
 Inclusive respirator (anti fog)  
 Diecast aluminium body  
 Fixtures - 304 stainless steel  
 Operating temperature -10° ~ +55°  
 Beam Angle 60°, 90° & 120°  
 Lens Material: Polycarbonate  
 Warranty - 5 Years

## FL SERIES OPTIONAL EXTRAS

Motion sensing control  
 Daylight sensor control  
 Retrofit bracket mounting

CE | RoHS | UL | NHRS

Part No	HM 50W	HM 100W	HM 244W	HM 488W
Wattage	50W	100W	244W	488W
Chipset	Philips			
LED Driver	Meanwell			
Surge Protection	10 kV			
Input Voltage	85 - 265 VAC 50Hz / 60Hz PF $\geq$ 0.95			
Luminos Efficacy	120 lm/W			
CCT	5,000K   6,000K			
CRI	RA>80			
Beam Angle	120°°			
IP Rating	IP 65			
Certification	CE   RoHS   UL   FC			

