

# PL - SERIES



## LUMINAIRE CHARACTERISTICS

100 - 277 Vac 50-60 Hz PF  $\leq$  0.95  
 50,000 Hours Lifespan 30° C @ L70  
 Energy Savings between 50 - 75%

Drop in panel for suspended ceiling  
 Aluminium body White  
 Fixtures - 304 stainless steel  
 Operating temperature -10° ~ +55°  
 Beam Angle 120°

Warranty - 5 Years

## OPTIONAL EXTRAS


Motion sensing control  
 Daylight sensor control

CE | RoHS | UL | FC

Part No	PL 40 Gold PD	PL 60 Gold PD
Wattage	40W	60W
Size	600mm x 600mm	1200mm x 600mm
Lumens (lm)	4,400 Lumens	6,600 Lumens
LED Driver	External Driver	
Configuration	Side lit LED with internal diffuser	
Surge Protection	2 kV	
Input Voltage	100-277 Vac 50Hz PF $\geq$ 0.95	
Luminous Efficacy	110 lm/W	
CCT	4,000K   6,000K	
CRI	RA >70   RA >80	
Beam Angle	120°	
IP Rating	IP 22	
Certification	CE   RoHS   UL   FC	




Hanging



Embedded



Surface Mounted



Embedded with coil spring