



T8 PLATINUM SERIES HO

LUMINAIRE CHARACTERISTICS

100 - 277 Vac 50-60 Hz PF \leq 0.93
 50,000 Hours Lifespan 30° C @ L70
 Energy Savings between 50 - 75%

Rotatable ends
 Plastic body and diffuser
 Fixtures - 304 stainless steel
 Operating temperature -10° ~ +55°
 Beam Angle 120°

Warranty - 5 Years

T-BAY OPTIONAL EXTRAS

Motion sensing control
 Daylight sensor control
 1 - 10V dimming control
 Retrofit to existing housing
 Rotatable end for perfect installation

CE | RoHS | UL | FC

Part No	TB 27W	TB 32W
Wattage	27W	32W
Luminos Flux	3,240 lm	3,840 lm
Size	1,200mm (4')	1,500mm (5')
Chipset	Philips / Epistar	
LED Driver	Factory OEM	
Surge Protection	2 kV	
Input Voltage	100-277 Vac 50Hz PF \geq 0.93	
Luminos Efficacy	110 lm/W	
CCT	4,000K 5,000K 6,000K	
CRI	RA >70 RA >80	
Beam Angle	120°	
IP Rating	IP 22	
Certification	CE RoHS UL FC	



LED T8 Tube Lights - Photometrics

